

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
22 February 2001 (22.02.2001)

PCT

(10) International Publication Number  
**WO 01/12329 A1**

(51) International Patent Classification<sup>7</sup>: B01L 3/02 // A61M 5/31

AVISON, Gerald [GB/GB]; 59 Victoria Park, Cambridge CB4 3EJ (GB).

(21) International Application Number: PCT/GB00/03142

(74) Agent: GILL JENNINGS & EVERY; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).

(22) International Filing Date: 15 August 2000 (15.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
99306463.3 17 August 1999 (17.08.1999) EP

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (*for all designated States except US*): THE TECHNOLOGY PARTNERSHIP PLC [GB/GB]; Melbourn Science Park, Cambridge Road, Melbourn, Royston, Herts SG8 6EE (GB).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): EDWARDS, Richard, Kelby [GB/GB]; 7 Leys Walk, Hauxton, Cambridge CB2 5HZ (GB). CASSELLS, John [GB/GB]; The Technology Partnership plc, Melbourn Science Park, Cambridge Road, Melbourn, Royston, Herts SG8 6EE (GB). MOUNTENEY, Nicholas, Ian [GB/GB]; 30A Owl Way, Hartford, Huntingdon, Cambridgeshire (GB).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SAMPLING/DISPENSING DEVICE WITH PLUNGER AND HOUSING SET ONTO PLUNGER



(57) Abstract: A positive displacement type substance sampling and dispensing device comprises a central plunger formed from a first material. A plunger housing is formed from a second material having a melting point lower than the first material, or otherwise being capable of being moulded around the first material, the housing being formed by moulding and setting the second material on to the surface of the plunger so that the plunger can slide in the housing to draw a substance into it.

## SAMPLING/DISPENSING DEVICE WITH PLUNGER AND HOUSING SET ONTO PLUNGER

This invention relates to a positive displacement type substance sampler/dispenser.

5        One example of such a dispenser is a plunger-type pipette. Such a pipette is in common usage. It generally comprises an outer cylindrical housing having a central bore in which a plunger sits. The plunger can be slid within the bore to either dispense a substance, such as a  
10    fluid or particulate matter, from an orifice in one end of the housing or, if slid in the opposite direction, to draw a fluid or particulate matter into the housing. Such a dispenser has particular benefits in that it can draw up and dispense substances with a high degree of accuracy.  
15    Devices in current use do, however, have problems associated with them.

Firstly, it is extremely difficult to produce a device which has a parallel housing bore, meaning that the relationship between the volume of the substance drawn up  
20    or dispensed is not linearly relative to the amount of displacement of the plunger. This is particularly true for low volume devices. Furthermore, it is extremely difficult to produce a bore to a level of accuracy which ensures that there is a tight fit between the plunger and the bore wall,  
25    meaning that fluid can pass around the edges of the plunger, leading to a reduction in sampling/dispensing accuracy, and leading to a risk of leakage.

The piston is typically slightly oversize for the bore such that it forms an interference fit for sealing. To  
30    accommodate this, and to allow for the draft angle on the bore, either the piston or the bore may be made from a compliant material. Examples are medical syringes having rigid polystyrene bores and rubber piston ends, or stiff polypropylene pistons with a compliant thin-walled bore.  
35    An alternative sealing arrangement is to provide a lip seal at the end of the piston. These constructions have many disadvantages. In general, compliant materials cannot be

used where chemical resistance is required; it becomes increasingly difficult to injection mould bores as the diameter is reduced such that devices capable of accurate dispensing over the nanolitre range are not possible; the  
5 need for a draft angle and conventional moulding techniques limits the practical length and thus the dynamic range of the pipette; and the manufacture of pistons with lip seals becomes increasingly difficult as the diameter is reduced below 1 mm.

10 Thus, present methods of construction are not suited to long bore, high accuracy, low cost and sub-microlitre devices.

Other problems associated with such devices includes the fact that they are difficult to handle automatically,  
15 their manufacture is costly, and it is often difficult to alter the materials from which the plunger and housing are made without changing moulding tooling for both components.

According to a first aspect of the present invention, there is provided a positive displacement type substance  
20 sampling and dispensing device comprising:

a central plunger formed from a first material; and  
a plunger housing formed from a second material, the housing being formed by moulding and setting the second material on to the surface of the plunger so that the  
25 plunger can slide in the housing to draw a substance into it.

The first material may be metal, plastic, ceramic or other suitable material. The plunger may be formed from drawn wire or extruded material to ensure that it has a  
30 uniform diameter. The housing may be moulded onto the plunger by injection moulding, welding, coextrusion, casting, dip coating etc.

The materials may be selected such that, preferably, the material of the piston is stiffer and/or has a lower  
35 thermal expansion coefficient than the material of the bore. If heat is applied during manufacture, such as using molten plastic to form a bore around a metal wire, the bore

will progressively tighten around the piston as the device cools down, thus forming a better seal. If the piston can be maintained at a lower temperature than the material of the bore during forming, it is possible to get further improved sealing because the piston will have expanded even less with respect to the bore. The piston may be actively cooled, or may exploit a higher thermal conductivity or specific heat capacity property than the material of the bore.

During its manufacture, the device may be attached or incorporated into a flexible strip or other backing to which further devices are attached for ease of automated handling.

The flexible strip may have sprocket holes to drive and align the pipettes.

Alternatively, the devices may be manufactured as single discrete pipettes. The pipettes are operated by gripping both the plunger housing and plunger of the pipette and moving the plunger within the bore in the same way as a conventional positive displacement pipette. This operation may be performed by a manual or automatic device. The devices may be used singly or in multiples with or without a backing strip.

The material of the strip may itself form part or all of the housing of the device.

The housing may be formed so that at one end of the device there is provided a frangible tip which can be removed before use to prevent contamination of the device prior to use.

Alternatively, the device may be formed so that it has a heat sealable tip, allowing for the loading of the apparatus with a substance, the substance being sealed in place by sealing of the tip.

The device may also be incorporated into fluidic devices such as "chip-based" analytical devices, chemical synthesizers and sensors to provide a means of forming capillaries, valves and pumps, for example.

The device may have plural plungers arranged on different axes and each sliding within a different region of the housing, the different regions of the housing being joined at a central common core adjacent to an aperture.

5 By forming the housing around the plunger the cost of manufacture of the device is reduced considerably. Furthermore, such a device has a highly effective seal between the plunger and the housing, and can also be ensured of having a uniform cylindrical wall, even if it is  
10 arranged for the dispensing/sampling of very small samples.

The device may be formed by moulding the bore round a drawn wire such that it produces a pipette with a perfectly cylindrical bore throughout. In use, the drawn wire may be projected beyond the tip of the device to pierce the seal  
15 of a storage vessel or to act as an ultrasonic probe or electrode for automatic level sensing. A second conductor may be provided parallel to the piston to act as a counter electrode.

The bore may be formed around a piston which has had  
20 its tip ground to a shaped point. This provides for an aperture that is a smaller diameter than the bore at the tip of the device, which is important for retaining liquid in larger bore devices.

One example of the present invention will now be  
25 described with reference to the accompanying drawings, in which:

Figure 1 is a schematic cross-sectional view of a known sampling/dispensing device;

Figure 2 is a side cross-sectional view of a device  
30 according to the present invention during a first stage of manufacture;

Figure 3 is a side cross-sectional view of a device according to the present invention after manufacture;

Figure 4 is a side view of a number of the devices  
35 according to the present invention attached to a flexible strip for ease of handling;

Figure 5 is a side cross-sectional view of a further example of the present invention;

Figure 6 is a perspective view of a number of the devices according to the present invention attached to a flexible strip;

Figure 7 shows the results of volumetric accuracy trials performed with one example of the present invention; and

Figure 8 shows photo-micrographs of a cross section of a pipette made by the process of example 1.

Referring to Figure 1, a prior art positive displacement-type pipette has an outer housing 1 which has a plunger 2 slidably retained therein. The plunger 2 can be moved to draw a sample into the housing 1 or expel a sample from the housing 1 via an aperture 3. The plunger 2 has a head 4 formed from relatively hard material and which is resilient enough to compensate for a variation in housing diameter with respect to the position of the plunger 2 within the housing. The disadvantages of this device, in terms of difficulty of manufacture, inaccuracies and leakage problems, are discussed above.

Figure 2 is a side cross-sectional view of a device 10 in accordance with the present invention during manufacture. The device 10 has a central plunger 12, in this example formed from drawn metal, and an outer housing 11. The outer housing 11 is moulded onto the plunger 12. If a thermoplastic (for example, polyethylene or polypropylene) is used to form the outer housing the plunger should be formed from a material with a higher melting point and preferably lower thermal expansion coefficient than the housing. The plunger, may for example, be made of metal, glass, plastic or ceramic. The housing may also be formed from a thermoset material (for example, silicone rubber or polyurethane resin) or a thermoplastic dissolved in solvent (for example polycarbonate or polyvinylchloride in solvent) in which case the plunger material need not have a higher melting

point than the housing. It is preferable to use a thermoset that shrinks on curing.

The housing 11 may be formed by injection moulding, extrusion, or any other well known casting, ultrasonic, welding, dip-coating, co-extrusion, powder coating, thermoforming, spraying forming technique. Once the housing 11 has cooled and set the device can be trimmed to length. In use the plunger 12 can be drawn into the housing, leaving an aperture 13 and an inner core 14 into which a sample can be drawn during use. The inner core 14 is a uniform cylinder as it corresponds to the outer surface of the plunger 12. Furthermore, it is in extremely close engagement with the plunger 12 because of the moulding techniques employed.

Figure 4 shows how the device 10 of the present invention may be attached to one or more flexible strips 15 for ease of handling. In particular, such an arrangement is handled very easily by automated machinery. In practice, because of the extremely low cost nature of the manufacture of the device 10, it can be treated as a disposable item in use.

Variations of the construction of the device 10 are possible. Firstly, the housing 11 may be formed over the end of the plunger 12 and arranged so that, in use, it has a frangible region which can be snapped off just prior to device use to prevent contamination of the plunger end. Furthermore, the device 10 may be provided with a heat sealable region adjacent to the aperture 13, so that a substance can be placed in the core 14 of the device 10 and sealed therein. This provides a sealed device that, once the end is cropped off, can meter and deliver the contents without loss.

A further alternative arrangement is shown in Figure 5. In this arrangement, plural plungers 12 have a outer housing 11 formed thereon. All of the plungers 12 are able to access a common core 14 and tip 13. By withdrawing the pistons, capillary paths are created in the device. Liquid

can be drawn up and moved through the system very precisely by moving the pistons. Where capillaries intersect the pistons may be operated as active valves to stop or regulate flow. A viewing window (not shown) may be incorporated into devices to allow the contents to be analysed by a detector. Such an arrangement provides for an extremely cost effective multiple sample withdrawal and dispensing arrangement that still has an high degree of sampling/dispensing accuracy and extremely low leakage.

This type of arrangement is not limited to the simple example shown. A multitude of pumps, capillaries and valves may be incorporated into three dimensional fluidic devices such as "chip-based" analytical devices, chemical synthesisers and sensors using the method of the invention.

There are now described three examples which have proved to be particularly advantageous.

#### Example 1

Figure 4 shows a device constructed according to the present invention. Hard drawn and polished stainless steel wire (British Standard 2056 302S26) of 0.40 mm diameter is inserted into high density polyethylene (HDPE) tubing of 0.43 mm ID and 0.66 mm OD. The tubing length is chosen as 23 mm and the wire length as 30 mm, to leave 7 mm of wire protruding. This tubing is placed across a tape 30 mm wide, made of 0.175 mm polypropylene film. The tubing with wire insert is then welded onto the backing tape using a hemi-cylindrical ultrasonic weld horn along the length of the plastic tube. This applies pressure and melts the plastic tube such that the tube material flows around the wire. This eliminates the 0.03 mm clearance between the wire and the tubing stock. A pipette is thus formed and is simultaneously welded to the backing film in one operation. Multiple pipettes can be formed in a continuous step-and-repeat process.

The tape can then be die-cut to crop the tubing and wire to form the pipette shapes and sprocket holes in one operation.



The backing tape is cut to provide slender pipettes.

Pipettes may be cut from the backing tape and used singly, or may be retained on the backing tape and used in multiples. The backing tape pitch was chosen to be a  
5 multiple of 2.25 mm (in this case 4.5 mm) to match the pitch of standard 96, 384 and 1536-well microtitre plates.

An aspirate/dispense head can be constructed to grip the backing tape or barrel and pistons independently, and to drive the pistons up and down under user or automatic  
10 control to achieve metering(not shown). Volumetric accuracy trials were performed with the prototype device by aspirating 100, 200, 300, 400 and 500 nl samples of writing inks and dispensing them into dry receptacles with tipping off. The results were determined gravimetrically and are  
15 shown in figure 7. This shows that even non-optimised devices following this invention are capable of accurately aspirating and dispensing samples as small as 100 nl.

Trials with prototype devices of the above construction were carried out to test their performance as  
20 storage devices. 100 nl of air was drawn into each device, followed by 100 nl of water and finally another 100 nl of air. Devices were tested with open and sealed ends. The ends were sealed by dipping into hot wax, hot melt glue or by heat welding them closed. Samples were stored for 30  
25 days at room temperature, -20°C and -74°C. The open-ended pipettes lost weight rapidly at room temperature, losing all the samples in six hours. All other samples showed no detectable weight loss over the test.

The advantage of this approach for storage is that all  
30 of the material stored can be recovered and the storage device can also be used to meter and dispense the stored sample.

Figure 8 shows a photomicrograph of a cross-section of a pipette made by the process of example 1. The 0.3 mm  
35 diameter wire has been withdrawn. The out-of-round distortion was caused by the blade used to cut the section.

On re-inserting the wire plunger the device assumes a circular cross-section.

A further device was made by the method above, but using polyethylene-coated PET film for the backing tape.  
5 The PET layer provides a stiffer backing tape more suited for mechanical feed.

#### Example 2

A device according to present invention was constructed by insert moulding 0.5 mm diameter stainless  
10 steel wire into mould-making grade silicone rubber. A mould was made from three 3 mm thick aluminium sheets sandwiched between two 1 mm thick sheets of glass such that a void 100 mm long, 20 mm high and 3 mm thick was formed. The assembly was held together with spring clips and the  
15 top of this void was open to allow filling with resin. An array of stainless steel wires was suspended above the mould with the ends of the wires protruding to the bottom of the mould. Silicone resin was poured into the mould and allowed to cure. Once set, the clips were released and the  
20 glass sides taken off the mould to allow the device to be removed. After shaping the pipettes with a knife the wires were cropped to length to form pistons. Operation of the resulting prototype demonstrated suitable function as a pipette.

#### 25 Example 3

A device according to the present invention was constructed by sandwiching stainless steel entomology pins (0.38 mm diameter, 38 mm long, size 00) between  
polypropylene tapes 0.2 mm thick by 30 mm wide 300 mm long.  
30 The pins were laid across one plastics material and the second plastic tape was over-laid to form a sandwich. The plastic sheets were joined together and heat-welded around and along the length of each individual pin between two hemi-cylindrical heated formers. This caused the  
35 polypropylene to flow around the pins, thus forming a barrel around each piston. The tape was then cut to form an array of pipettes following the method of Example 1.

**Example 4**

A stiff stainless steel wire of 0.4 mm diameter (EN304, BS1554 or similar) was coated with an extruded polyethylene (PE) sheath to give an overall diameter of  
5 0.80 mm.

Conventional equipment for making insulated electrical wire was used to make the coated wire, but with the process and settings revised to accommodate the wire hardness and the polyethylene coating material. This coated wire was  
10 straightened and cut into pipettes of 20 mm length. The coating was stripped off from one end of each pipette to provide a shank 4 mm long. This shank may be gripped to move the plunger in the barrel of the pipette. Conventional electrical wire can be used to make devices of  
15 the present invention, but performance is poor because the wire is not stiff enough to allow operation against a tight seal, copper is not desirable as a material in contact with chemical and biological samples, and the PVC coating does not have the desirable properties. The pipette thus formed  
20 can be used singly, or preferably is joined transversely to a backing strip.

A backing strip was formed by cutting polyester/Surlyn/EVA film (thickness 125 $\mu$ m overall) to form a carrier tape with tabs along one edge and sprocket holes  
25 for transport (figure 4). Pipettes were ultrasonically welded to this carrier tape at 4.5 mm intervals. Strips of pipettes or individual pipettes can be cut off this carrier tape for subsequent use.

CLAIMS

1. A positive displacement type substance sampling and dispensing device comprising:
  - 5 a central plunger formed from a first material; and
  - a plunger housing formed from a second material the housing being formed by moulding and setting the second material on to the surface of the plunger so that the plunger can slide in the housing to draw a substance into
  - 10 it.
2. A device according to claim 1, wherein the plunger is formed from drawn wire or extruded metal.
- 15 3. A device according to claim 1, wherein the first material is one of metal, plastic and ceramic.
4. A device according to any one of the preceding claims, wherein the second material is plastics material.
- 20 5. A device according to any one of the preceding claims, wherein the plunger is actively cooled during moulding.
6. A device according to any one of the preceding claims, wherein the first material has a higher thermal conductivity and/or specific heat capacity than the second material.
- 25 7. A device according to any one of the preceding claims, wherein the housing is moulded onto the plunger by one of injection moulding, welding, coextrusion casting and dip coating.
- 30 8. A device according to any preceding claim, attached to a flexible strip, to which further devices are attached in use.
- 35

9. A device according to any claim 8, wherein the strip has sprocket holes to drive and align the pipettes.

5 10. A device according to any preceding claim, wherein the housing is formed so that at one end of the device there is provided a frangible tip which can be removed before use.

10 11. A device according to any of claims 1 to 11, wherein the device is formed so that it has a heat sealable tip.

15 12. A device according to any proceeding claim comprising plural plungers arranged on different axes and each sliding within a different region of the housing, the different regions of the housing being joined at a central common core adjacent to an aperture.

Figure 1

1/6




Figure 2






Figure 3




2/6

Figure  
4



3/6

Figure 5





4/6

Figure 6




Figure 7-  
Volumetric data for prototype pipettes






Figure 8



# INTERNATIONAL SEARCH REPORT

Intern 1st Application No

PCT/GB 00/03142

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 B01L3/02 //A61M5/31

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B01L A61M G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>US 5 658 258 A (KNEER ROLAND ET AL) 19 August 1997 (1997-08-19) column 1, line 34 -column 1, line 48 column 1, line 62 -column 1, line 65 column 2, line 3 -column 2, line 9 column 2, line 17 -column 2, line 24 column 3, line 18 -column 3, line 36 column 4, line 41 -column 5, line 9 column 5, line 31 -column 5, line 40 column 5, line 46 -column 5, line 57 figures 1-8</p> <p style="text-align: center;">--- -/--</p>	1,3,4,7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

27 October 2000

Date of mailing of the international search report

03/11/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Koch, A

# INTERNATIONAL SEARCH REPORT

Intern 1a1 Application No

PCT/GB 00/03142

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 443 227 A (ITO CORP) 28 August 1991 (1991-08-28) column 1, line 19 -column 1, line 52 column 2, line 31 -column 2, line 44 column 3, line 41 -column 4, line 6 column 5, line 32 -column 6, line 5 figures 1,5 ---	1-3
A	EP 0 226 867 A (HAMILTON BONADUZ AG) 1 July 1987 (1987-07-01) page 1, line 1 -page 2, line 2 page 2, line 19 -page 2, line 31 page 4, line 2 -page 4, line 24 page 5, line 12 -page 5, line 36 page 6, line 12 -page 6, line 25 page 11, line 18 -page 14, line 12 figures 1-10 ---	1,8,9
X	US 3 766 785 A (SMERNOFF R) 23 October 1973 (1973-10-23) column 1, line 61 -column 2, line 38 column 4, line 15 -column 4, line 25 column 5, line 8 -column 5, line 51 figures 1,7,8 ---	1,7
X	WO 99 34931 A (CARTESIAN TECHNOLOGY INC) 15 July 1999 (1999-07-15) page 10, line 18 -page 10, line 26 page 10, line 36 -page 11, line 3 page 11, line 14 -page 11, line 15 page 24, line 26 -page 24, line 34 figures 2,4,10 ---	1-4
Y		11
X		12
Y	WO 92 20778 A (KINDCONI PTY LIMITED) 26 November 1992 (1992-11-26) page 6, line 2 -page 6, line 32 figures 1,2 -----	11

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/03142

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5658258 A	19-08-1997	DE 4433198 C EP 0701864 A	13-06-1996 20-03-1996
EP 0443227 A	28-08-1991	AU 617589 B AU 4992690 A US 5063025 A	28-11-1991 05-09-1991 05-11-1991
EP 0226867 A	01-07-1987	CH 671526 A AT 74539 T CA 1321985 A DE 3684767 A ES 2030656 T JP 2528297 B JP 62191049 A US 4967604 A US 4830832 A	15-09-1989 15-04-1992 07-09-1993 14-05-1992 16-11-1992 28-08-1996 21-08-1987 06-11-1990 16-05-1989
US 3766785 A	23-10-1973	CA 976929 A CH 336620 A CH 440768 A DE 2248573 A DE 1191140 B FR 2015747 A FR 2156019 A FR 1317488 A FR 1492062 A GB 1411424 A GB 720204 A GB 815199 A GB 962356 A GB 1148241 A GB 1148242 A US 1747523 A US 3853012 A US 2517689 A US 2685800 A US 2724275 A US 2994349 A US 3244009 A US 3285296 A US 3500689 A	28-10-1975   12-04-1973  30-04-1970 25-05-1973 08-05-1963 22-11-1967 22-10-1975      18-02-1930 10-12-1974 08-08-1950 10-08-1954 22-11-1955 01-08-1961 05-04-1966 15-11-1966 17-03-1970
WO 9934931 A	15-07-1999	US 6063339 A AU 2211999 A EP 1044072 A	16-05-2000 26-07-1999 18-10-2000
WO 9220778 A	26-11-1992	NONE	